

440E Lifeline 4 Stainless Steel Cable (Rope) Pull Switches

440E Lifeline 4 Stainless Steel Cable (Rope) Pull Switches



Features

- Rugged, corrosion-resistant 316 stainless steel construction
- IP66/IP67 enclosure rating allows use in harsh environments
- Switches up to 75m cable span
- Lid mounted emergency stop button, designed to conform with ISO 13850

Product Selection

440E Lifeline 4 Stainless Steel Cable (Rope) Pull Switches

System Length	Safety Contacts	Auxiliary Contacts	Model	Conduit Entry	Cat. No.
≤ 75 m	2 N.C. direct opening action	2 N.O.	Lifeline 4 Stainless steel	3 x M20	440E-L22BNSM
≤ 75 m	2 N.C. direct opening action	2 N.O.	Lifeline 4 Stainless steel	Quick-Disconnect	440E-L22BNSL

Installation Kits

Description	Material	Length	Cat. No.
Lifeline 4 Stainless Steel Installation Kit -Comprises: 1 x length of cable (rope), 2 x grippers, 1 x tensioner and quantity of eyebolts.	Rope = Steel core with polypropylene sheath	5 m	440E-A13194
	Thimble = Stainless steel 304	10 m	440E-A13195
	Rope Grips = Stainless steel 304	15 m	440E-A13196
	Tensioner = Stainless steel 316	20 m	440E-A13197
	Eyebolts = Stainless steel 304	30 m	440E-A13198
	Nuts and washers = Stainless steel	50 m	440E-A13199
		75 m	440E-A13200